### **BRAKES & SUSPENSION**

### +44 (0) 1885 488 488

LIGHTING SWITCHES IGNITION WIRING HEATERS & ELECTRIC FANS ACCESSORIES BODY HARDWARE BRAKES & **SUSPENSION** CLUTCH KITS

EXHAUSTS

FIXINGS

FUEL


SYSTEMS &

MIRRORS

POWER

STEERING

SEATS &



Andre Hartford Shock Absorbers are suitable for use on all makes of vintage car, and for all types of road and track events. This is the latest high efficiency model



Suitable for use on cars up to:

1 tonne

2 tonne

 $1^{1/2}$  tonne

2 tonne

Sizes

3<sup>1</sup>/<sub>2</sub>" single disc

3<sup>1</sup>/<sub>2</sub>" multiple disc

4<sup>1</sup>/<sub>2</sub>" multiple disc

 $4^{1/2}$ " single disc

New improved friction discs, special impregnated, to resist the weather a	
damping action under the most extre	
A self locking indicator clearly	

registering the degree of adjustment which cannot work loose

Dual control springs on either side of the shock absorber giving an accurate pressure adjustment New type non-corrosive friction plates unaffected by weather conditions

065.054

065.055

065.065

065.066

**FRICTION DISC** 

2.5mm thick for  $3^{1/2}$ 

4.5mm thick for 31/2"

2.5mm thick for  $4^{1/2}$ "

4.5mm thick for  $4^{1/2}$ "

WASHERS & WIPERS OIL & AIR CARE & STORAGE

OIL, GREASE & FLUIDS PAINT & ANTI-RUST



### **BUSHES**

£

Rubber Bush for  $3^{1}/_{2}$ " and  $4^{1}/_{2}$ " (shown left) 065.064

You

O)

Centre Bush for 3<sup>1</sup>/<sub>2</sub>" and  $4^{1}/_{2}$ "(shown right) 065.056

9

**BRASS DISC** For 3<sup>1</sup>/<sub>2</sub>" 065.061 For 4<sup>1</sup>/<sub>2</sub>" 065.069



For 3<sup>1</sup>/<sub>2</sub>" and 4<sup>1</sup>/<sub>2</sub>" 065.063



**CENTRE BOLT & NUT** Single disc for  $3^{1/2}$ " and  $4^{1/2}$ " 065.057

Multiple disc  $3^{1/2}$ " and  $4^{1/2}$ " 065.058

**ANDRE HARTFORD** Minimal friction Andre With backplate Hartford replacement friction For  $3^{1}/2^{2}$ discs. These are designed to improve your vehicle's ride 065.060 quality by reducing friction For 4<sup>1</sup>/<sub>2</sub>" within the shock absorber. 065.068 5mm thick for 4<sup>1</sup>/<sub>2</sub>" Centre hole 1<sup>1</sup>/<sub>2</sub>" 5mm thick for 3<sup>1</sup>/2"

065.073

065.072

Centre hole 11/2"

STAR SPRING

**065.059** For 3<sup>1</sup>/<sub>2</sub>"

**065.067** For 4<sup>1</sup>/<sub>2</sub>"

**WEVINTAGE & CLASSIC** 



NUTS Special Castle Nut 1/2" BSF, deep slotted, countersunk, (shown left) 065.052

INDICATOR DIAL

Standard 1/2" BSF Full Nuts (shown right) 065.053

**POINTER & LOCKING** TAG For 3<sup>1</sup>/<sub>2</sub>" and 4<sup>1</sup>/<sub>2</sub>"

(1 tonne = 20 cwt)

All arms are fitted with rubber bushes. These require no lubrication or attention, always

remain silent in action, and have a long life

065.062



**CHASSIS MOUNTING** BOLT

Overall length 82.5mm, length of hexagonal portion 4.75mm 065.049

Overall length 97mm, length of hexagonal portion 27mm 065.051

Overall length 111mm, length of hexagonal portion 17.5mm 065.050



ANDRE HARTFORD 3 1/2 IN DIAMETER 1 BLADE INTO 2

Suitable for use on all makes of vintage car. This is the latest high efficiency model with improved friction discs 3 1/2 diameter, self locking indicator, dua control springs and non-corrosive friction plates. Both arms are the same length and are fitted with rubber bushes. One blade into two blades at the friction end. Suitable for smaller vehicles up to 1,000 kg weight MADE TO ORDER 3-6 WEEKS

Туре	Part No	Туре
1 Blade into 2 (4 1/2 in arms)	065.001	2 Blades into 3 (4 1/2 in arr
1 Blade into 2 (5 in arms)	065.002	2 Blades into 3 (5 in arms)
1 Blade into 2 (5 1/2 in arms)	065.003	2 Blades into 3 (5 1/2 in arms
1 Blade into 2 (6 in arms)	065.004	Blades into 3 (6 in arms)
1 Blade into 2 (6 1/2 in arms)	065.005	2 Blades into 3 (6 1/2 in arms)
1 Blade into 2 (7 in arms)	065.006	2 Blades into 3 (7 in arms)
1 Blade into 2 (7 1/2 in arms)	065.007	2 Blades into 3 (7 1/2 in arms)
1 Blade into 2 (8 in arms)	065.008	2 Blades into 3 (8 in arms)
1 Blade into 2 (8 1/2 in arms)	065.009	2 Blades into 3 (8 1/2 in arms)
1 Blade into 2 (9 in arms)	065.010	2 Blades into 3 (9 in arms)



ANDRE HARTFORD 4 1/2 IN DIAMETER 1 BLADE INTO 2

Suitable for use on all makes of vintage car. This is the latest high efficiency model with improved friction discs 4 1/2' diameter, self locking indicator, dua control springs and non-corrosive friction plates. Both arms are the same length and are fitted with rubber bushes. One blade into two blades at the friction end. Suitable for vehicles from 1,000 to 1250 kg weight MADE TO ORDER 3-6 WEEKS

Type Part No				
		Туре	Part No	
1 Blade into 2 (4 1/2 in arms)	065.023	2 Blades into 3 (4 1/2 in arms)	065.036	
1 Blade into 2 (5 in arms)	065.024	2 Blades into 3 (5 in arms)	065.037	
1 Blade into 2 (5 1/2 in arms)	065.025	2 Blades into 3 (5 1/2 in arms)	065.038	
1 Blade into 2 (6 in arms)	065.026	2 Blades into 3 (6 in arms)	065.039	
1 Blade into 2 (6 1/2 in arms)	065.027	2 Blades into 3 (6 1/2 in arms)	065.040	
1 Blade into 2 (7 in arms)	065.028	2 Blades into 3 (7 in arms)	065.041	
1 Blade into 2 (7 1/2 in arms)	065.029	2 Blades into 3 (7 1/2 in arms)	065.042	
1 Blade into 2 (8 in arms)	065.030	2 Blades into 3 (8 in arms)	065.043	
1 Blade into 2 (8 1/2 in arms)	065.031	2 Blades into 3 (8 1/2 in arms)	065.044	
1 Blade into 2 (9 in arms)	065.032	2 Blades into 3 (9 in arms)	065.045	
1 Blade into 2 (9 1/2 in arms)	065.033	2 Blades into 3 (9 1/2 in arms)	065.046	
1 Blade into 2 (10 in arms)	065.034	2 Blades into 3 (10 in arms)	065.047	

FOR LATEST PRICES REFER TO WEBSITE

**SKVINTAGE & CLASSIC** 

FOR LATEST PRICES REFER TO WEBSITE

# SHOCK ABSORBERS



#### ANDRE HARTFORD 3 1/2 IN DIAMETER 2 BLADE INTO 3

Suitable for use on all makes of vintage car. This is the latest high efficiency nodel with improved friction discs 3 1/2 diameter, self locking indicator, dua control springs and non-corrosive friction plates. Both arms are the same length and are fitted with rubber bushes. Two blades into three blades at the friction end. Suitable for medium vehicles from 1,250 to 1,500 kg weight MADE TO ORDER 3-6 WEEKS



#### ANDRE HARTFORD 4 1/2 IN DIAMETER 2 BLADES INTO 3

Suitable for use on all makes of vintage car. This is the latest high efficiency model with improved friction discs 4 1/2' diameter, self locking indicator, dual control springs and non-corrosive friction plates. Both arms are the same length and are fitted with rubber bushes. Two blades into three blades at the friction end. Suitable for vehicles over 1,500 kg weight MADE TO ORDER 3-6 WEEKS



SWITCHES

IGNITION

WIRING

HEATERS & ELECTRIC

BODY HARDWARE

#### **BRAKES &** SUSPENSION

CLUTCH KITS

EXHAUSTS

FIXINGS

FUFL SYSTEMS & FILTERS

MIRRORS

POWER STEERING

SEATS & SEAT BELTS

WASHERS & WIPERS

OIL & AIR

CARE & STORAGE

OIL, GREASE & FLUIDS

PAINT & ANTI-RUST



### SHOCK ABSORBERS

LIGHTING

SWITCHES

IGNITION

WIRING

HEATERS &

ELECTRIC

ACCESSORIES

HARDWARE

BRAKES &

**SUSPENSION** 

CLUTCH KITS

EXHAUSTS

FIXINGS

FUEL

SYSTEMS &

MIRRORS

POWER

STEERING

SEATS &

SEAT BELTS

WASHERS &

WIPERS

OIL & AIR

CARE &

STORAGE

OIL, GREASE

& FLUIDS

PAINT &

FANS

BODY

### +44 (0) 1885 488 488

### WWW.HOLDEN.CO.UK



# FRONT SHOCK ABSORBER

Girling shock absorber, replacement OE part, all steel construction, original ride characteristics, no adjustment required, made to have the perfect set-up for the Jaguar E Type. Correct RAF (BS633 sometimes referred to as squadron blue) deep blue/grey colour. New improved one piece bushes replaces the old two piece lower bush. Improved internals using modern materials. Guaranteed for 2 years. Use C9326 sleeve when fitting to lower

**C20011G** Front shock absorber

bush, as original.



#### ANDRE HARTFORD 4 1/2 IN DIAMETER 2 BLADES INTO 3 (6 IN **ARMS) ALUMINIUM**

Suitable for use on all makes of vintage car. This is the latest high efficiency model with improved friction discs 4 1/2' diameter, self locking indicator, dual control springs and non-corrosive friction plates. Both arms are the same length 6' and are fitted with rubber bushes. Two blades into three blades at the friction end.

Suitable for vehicles over 1,500 kg weight MADE TO ORDER 3-6 WEEKS ALUMINIUM

065.039A



C9326

LOWER SLEEVE Front Shock Absorber Lower Sleeve



**REAR SHOCK ABSORBER** Girling Jaguar E Type Rear Shock Absorber C25951G Rear shock absorber



065.657/S Steel



FOR 1/4" PIPE Male Pipe Nut 7/16" x 20 UNF 065.657 Brass



FOR <sup>1</sup>/<sub>4</sub>" PIPE Female Pipe Nut <sup>7</sup>/16" x 20 UNF. 065.658 Brass 065.658/S Steel

bleed pipe



065.670

**DOUBLE PIPE CLIP** 

065.671

For <sup>3</sup>/<sub>16</sub>" pipes. Plastic


**TRIPLE PIPE CLIP** 

065.672











# **BRAKE CALIPER KITS**



FOR LATEST PRICES REFER TO WEBSITE

**GIRLING 17/3 CALIPERS** Supplied with OEM spec brake pads.

SBS9293AG/1



### **BRAKE PIPE FITTINGS**



### **PURE COPPER PIPE**

Normally used on cars in the classic period. Meets BS2871 standard. The more usual size is  $\frac{3}{16}$ " outside diameter but we also offer  $\frac{1}{4}$ ". Sold in rolls of 7.62 metres (25 ft) 065.640 <sup>3</sup>/16" 065.641 <sup>1</sup>/4"



### **KUNIFER PIPE**

A top quality copper/nickel alloy is generally reckoned to be the best for braking systems. We offer both <sup>3</sup>/16" and <sup>1</sup>/4". Sold in rolls of 7.62 metres (25 ft) 065.642 <sup>3</sup>/16" 065.643 <sup>1</sup>/4" 065.642/S <sup>3</sup>/16" one metre roll

Up until about 1976 British and European cars mainly used UNF Brake Fittings. Brass unless stated



FOR <sup>3</sup>/<sub>16</sub>" PIPE Male Pipe Nut <sup>3</sup>/<sub>8</sub>" x 24 UNF 065.644 Brass 065.644/S Steel



f

ANTI-RUST



9

3-Way Connector, all ends threaded <sup>3</sup>/<sub>8</sub>" x 24 UNF. (Use three 065.644) 065.648

You

O)




FOR <sup>3</sup>/<sub>16</sub>" PIPE

065.645 Brass

065.645/S Steel

Female Pipe Nut <sup>3</sup>/8" x 24 UNF.

FOR <sup>3</sup>/<sub>16</sub>" PIPE 4-Way Connector, all ends threaded <sup>3</sup>/<sub>8</sub>" x 24 UNF. (Use four 065.644) 065.649



4-Way Connector, 3 ends threaded

<sup>3</sup>/<sub>8</sub>" x 24 UNF plus 1/8 NPT for switch.

(Use four 065.644 & switch 34765).

FOR <sup>3</sup>/<sub>16</sub>" PIPE

FOR <sup>3</sup>/<sub>16</sub>" PIPE

As fitted to MGA

065.651

**WINTAGE & CLASSIC** 

FOR 3/16" PIPE Male In-line Connector. both ends threaded <sup>3</sup>/8" x 24 UNF (Use two 065 645 065.646 065.646/S Steel



FOR <sup>3</sup>/<sub>16</sub>" PIPE Male Pipe Nut 7/16" x 20 UNF 065.650 065.650/S Steel



FOR LATEST PRICES REFER TO WEBSITE

# **BRAKE PIPE FITTINGS**



For <sup>3</sup>/16" pipes. Plastic

1/4" BLEED SCREW Bleed Screw <sup>1</sup>/<sub>4</sub>" x 28 UNF. Takes <sup>1</sup>/<sub>4</sub>" 065.664 Brass 065.664/S Steel



3/8" BLEED SCREW Bleed Screw <sup>3</sup>/<sub>8</sub>" x 24 UNF. Takes <sup>1</sup>/<sub>4</sub>" bleed pipe 065.665 Brass 065.665/S Steel



**'P' PIPE CLIP** For <sup>3</sup>/16" Pipe, Plastic 065.673



**'P' PIPE CLIPS** For <sup>5</sup>/16" pipe. Plastic 065.677

Clear plastic box containing:					
	Part No.	Amount	Part No.		
	065.644	2	065.665		
	065.645	1	065.646A		
	065.650	1	065.647		
	065.657	1	065.649		
	065.658	1	065.648		
	065.664	10	065.670		
	065.665	All the above	065.669		

### **GIRLING UP-RATED 4 POT BRAKE CALIPER KIT REPLACES**

Girling branded up-graded UK manufactured Front Brake Caliper Conversion Kit. UK manufactured four pot front brake caliper conversion kit in aerospace grade

7075 grade silver aluminium. Fitted with OEM spec modern seals and 303 grade stainless steel pistons and pins. The kit is directly compatible with the original suspension uprights without need for modification or additional brackets.



197

LIGHTING

SWITCHES

IGNITION

WIRING

HEATERS & ELECTRIC

ACCESSORIES

BODY HARDWARE

#### BRAKES & SUSPENSION

CLUTCH KITS

FXHAUSTS

FIXINGS

FUFL SYSTEMS & FILTERS

MIRRORS

POWER STEERING

SEATS & SEAT BELTS

WASHERS & WIPERS

OIL & AIR FILTERS

CARE & STORAGE

OIL, GREASE & FLUIDS

PAINT & ANTI-RUST

### **BRAKE CALIPER KITS**

### +44 (0) 1885 488 488

**GIRLING BRAKE CYLINDER AND** 

PISTON ASSEMBLY - REAR 1 5/8-

Girling brake cylinder and piston, 15/8" piston

diameter, New and improved genuine Girling

part. Original cast type body, with up-rated

stainless steel piston and improved modern

STAINLESS STEEL PISTON

64932065 Girling part number

seals. Made in Demark

7847G

### WWW.HOLDEN.CO.UK



**GIRLING UP-RATED 4 POT BRAKE CALIPER KIT REPLACES GIRLING 17/3 CALIPERS WITH NEW** VENTED DISCS

Girling branded up-graded UK manufactured Front Brake Caliper Conversion Kit. UK manufactured four pot front brake caliper conversion kit in aerospace grade 7075 grade silver aluminium. Fitted with OEM spec modern seals and 303 grade stainless steel pistons and pins. The kit is directly compatible with the original suspension uprights without need for modification or additional brackets.

Supplied with OEM spec brake pads.

CALIPERS WITH NEW VENTED DISCS

UK manufactured four pot front brake caliper

conversion kit in aerospace grade 7075 grade

silver aluminium. Fitted with OEM spec modern

seals and 303 grade stainless steel pistons and

Supplied with OEM spec brake pads and new

pins. The kit is directly compatible with the original

suspension uprights without need for modification

Brake Caliper Conversion Kit.

or additional brackets.

vented discs.

SBS9093AG

Girling branded up-graded UK manufactured Front

This kit cannot be fitted to standard 5" width wheels. 6" or above is recommended.



BODY HARDWARE

LIGHTING

SWITCHES

IGNITION

WIRING

HEATERS &

ELECTRIC

ACCESSORIES

FANS

#### BRAKES & **SUSPENSION**



PAINT &

ANTI-RUST



You

O)

>



#### **FRONT BRAKE CALIPER CONVERSION KIT -**ALUMINIUM 4 POT

Front Brake Caliper Conversion Kit -Manufactured in aerospace 7075 grade silver aluminium, with 'Girling' script embossed. Fitted with OEM spec modern seals and 303 grade stainless steel pistons and pins.

#### The kit is directly compatible with the original suspension uprights without need for modification or additional brackets.

Supplied with OEM spec brake pads. SBS9086AG



#### **GIRLING UP-RATED 4 POT BRAKE CALIPER KIT REPLACES GIRLING 14 AH** 100/6 3000 MK1 MK2 MORGAN PRE '92 Girling branded up-graded UK manufactured Front Brake Caliper Conversion Kit.

UK manufactured four pot front brake caliper conversion kit in aerospace grade 7075 grade silver aluminium. Fitted with OEM spec modern seals and 303 grade stainless steel pistons and pins. The kit is directly compatible with the original suspension uprights without need for modification or additional brackets.

with OEM spec modern seals and 303 grade stainless steel pistons and pins.

Supplied with  $\mathsf{OEM}$  spec brake pads. (also fit Triumph Spitfire)

### SBS9292AG



SBS9290AG

**GIRLING UP-RATED 4 POT BRAKE** 

**CALIPER KIT REPLACES GIRLING 14/** 

LOCKHEED CALIPERS FITTED TO MGB

Girling branded up-graded UK manufactured Front



Supplied with OEM spec brake pads. SBS9291AG

brackets



BRAKE CALIPER UPGRADE CONVERSION Brake caliper upgrade conversion -Kit of parts to convert drum brakes to discs - includes discs, pads, hubs and calipers. Wire wheel cars only



There are many options in the range please contact one of the sales team

		BRAKE CALIF	PER FITMENT LIST			
Vehicle Make Vehicle Model Vehicle Variant OEM Caliper Vented? Part Number						
on Martin	DB4		Dunlop 1	Non-Vented	*SBS9086	
in Healey	3000	Mk1 (BN7 & BT7)	Girling 14	Non-Vented	SBS9292AG	
in Healey	3000	Mk2 (BJ7, BN7 & BT7)	Girling 14	Non-Vented	SBS9292AG	
tin Healey	3000	Mk3 (BJ8)	Lockheed 4264-091/2	Non-Vented	SBS9291AG	
tin Healey	100/6		Girling 14	Non-Vented	SBS9292AG	
mler	V8-250		Dunlop 1	Non-Vented	SBS9086	
nler	V8-250		Dunlop 1	Vented	SBS9093AG	
man	Minx	1.5 (all) & 1.7(1967 on)	Girling 16	Non-Vented	SBS9291AG	
nan	Minx	1.6 (all) & 1.7 (to 1967)	Girling 16	Non-Vented	SBS9291AG	
nan	Super Minx	1962 on	Girling 16	Non-Vented	SBS9291AG	
iar	Е-Туре	Series 1 (3.8 litre)	Dunlop 1	Non-Vented	SBS9086	
ıar	Е-Туре	Series 1 (3.8 litre)	Dunlop 1	Vented	SBS9093AG	
ar	Е-Туре	Series 1.5 (4.2 Litre)	Dunlop 1	Non-Vented	SBS9086	
ar	Е-Туре	Series 1.5 (4.2 Litre)	Dunlop 1	Vented	SBS9093AG	
iar	Е-Туре	Series 2	Girling 17/3	Non-Vented	SBS9293AG/1	
ar	Е-Туре	Series 2	Girling 17/3	Vented	SBS9293AG	
ar	Е-Туре	Series 2 (2+2)	Girling 17/3	Non-Vented	SBS9293AG/1	
ar	Е-Туре	Series 2 (2+2)	Girling 17/3	Vented	SBS9293AG	
ar	Е-Туре	Series 3 inc V12	Girling 17/3	Vented	SBS9293AG	
ar	Mk 9		Dunlop 1	Non-Vented	SBS9086	
r	Mk1	2.4 litre	Dunlop 1	Non-Vented	SBS9086	
-	Mk1	3.4 litre	Dunlop 1	Non-Vented	SBS9086	
ar	Mk10	3.8 litre	Girling 17/3	Non-Vented	SBS9293AG/1	
ır	Mk10	4.2 litre	Girling 17/3	Non-Vented	SBS9293AG/1	
ar	Mk2		Dunlop 1	Non-Vented	SBS9086	
ar	Mk2		Dunlop 1	Vented	SBS9093AG	
ar	S-Type		Dunlop 2	Non-Vented	*SBS9086	
ar	XK140		XK150 conversion	Non-Vented	*SBS9330	
ar	XK150		Dunlop 1	Non-Vented	SBS9086	
en	FF	Mk 1	Dunlop 1	Non-Vented	SBS9086	
en	FF	Mk 2	Girling 17/3	Non-Vented	SBS9293AG/1	
n	Healey & GT		Girling 14	Non-Vented	SBS9292AG	
en	Interceptor	Mk 1	Dunlop 1	Non-Vented	SBS9086	
en	Interceptor	Mk 2	Girling 17/3	Vented	SBS9293AG	
en	Interceptor	Mk3	Girling 17/3	Vented	SBS9293AG	
sen	Interceptor SP V8		Girling 17/3	Non-Vented	SBS9293AG/1	
en	Interceptor SP V8		Girling 17/3	Vented	SBS9293AG	



FOR LATEST PRICES REFER TO WEBSITE

FOR LATEST PRICES REFER TO WEBSITE

Aluminium, 4 pot

SBS9086/1

Front Brake Caliper Conversion Kit

**WINTAGE & CLASSIC** 

# **BRAKE CONVERSION KITS**



### **BRAKE CONVERSION KITS**

### +44 (0) 1885 488 488

### WWW.HOLDEN.CO.UK

LIGHTING SWITCHES IGNITION WIRING HEATERS & ELECTRIC FANS ACCESSORIES BODY HARDWARF BRAKES & **SUSPENSION** CLUTCH KITS

FIXINGS

FUEL

SYSTEMS &

MIRRORS

POWER

STEERING

SEATS &

SEAT BELTS

WASHERS &

WIPERS

OIL & AIR

CARE &

STORAGE

OIL, GREASE

& FLUIDS

PAINT &

ANTI-RUST

		BRAKE CA	ALIPER FITMENT LIST		
Vehicle Make	Vehicle Model	Vehicle Variant	OEM Caliper	Vented?	
Lotus	Eclat	1980-1982	Girling 17/3	Non-Vented	SBS9293AG/1
MG	А	1600 & 1600 Mk2	Girling 17/3	Non-Vented	SBS9293AG/1
MG	A	Twin Cam	Dunlop 1	Non-Vented	SBS9086
MG	В		Lockheed	Non-Vented	
MG	В	GT	Lockheed	Non-Vented	
MG	С		Lockheed 4264-091/2	Non-Vented	SBS9291AG
Morgan	Four/Four	Pre 1992	Girling 14	Non-Vented	SBS9292AG
Morgan	Plus 4	Pre 1992	Girling 14	Non-Vented	SBS9292AG
Triumph	GT6	Mk1	Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	GT6	Mk2	Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	GT6	Mk3	Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	Herald	12/50	Girling 14	Non-Vented	SBS9292AG
Triumph	Herald	13/60	Girling 14	Non-Vented	SBS9292AG
Triumph	Spitfire	Mk3	Girling 14	Non-Vented	SBS9292AG
Triumph	Spitfire	Mk4	Girling 14	Non-Vented	SBS9292AG
Triumph	Spitfire	1500 TC	Girling 14	Non-Vented	SBS9292AG
Triumph	TR4	1962-1965	Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	TR4A		Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	TR5		Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	TR6		Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	Vitesse	2L Mk1	Lockheed 4264-091/2	Non-Vented	SBS9291AG
Triumph	Vitesse	Mk2	Lockheed 4264-091/2	Non-Vented	SBS9291AG

## **BRAKE CYLINDERS**



**GIRLING BRAKE CYLINDER AND PISTON** FRONT 2 1/8" PISTON DIAMETER -**STAINLESS STEEL PISTON** 

Girling brake cylinder and piston, 2 1/8" piston diameter, New and improved genuine Girling part. Original cast type body, with up-rated stainless steel piston and improved modern seals. Made in Demark. Girling part number 64932067.

Four cylinders per axle required, ie. two per wheel

You

9

O)

### 8777G





**GIRLING BRAKE CYLINDER AND PISTON REAR 1 1/2" PISTON DIAMETER -**STAINLESS STEEL PISTON

Girling brake cylinder and piston, 1 1/2" piston diameter, New and improved genuine Girling part. Original cast type body, with up-rated stainless steel piston and improved modern seals. Made in Demark. Girling part number 64932063.

Four cylinders per axle required, ie two per wheel

**WINTAGE & CLASSIC** 

### 8816G



TRIUMPH SPITFIRE MK IV/1500 REAR BRAKE CYLINDER (0.625 IN)

both with 0.625 in cylinders. Original Equipment Part No. GWC1202 065.838



#### GIRLING BRAKE CYLINDER AND PISTON **REAR 1 3/4" PISTON DIAMETER -**STAINLESS STEEL PISTON

Girling brake cylinder and piston, 1 3/4" piston diameter, New and improved genuine Girling part. Original cast type body, with up-rated stainless steel piston and improved modern seals. Made in Demark. Girling part number 64932066.

Four cylinders per axle required, ie two per wheel

8778G

### Rear Brake Cylinder for either side of Triumph Spitfire Mk IV and 1500 to FH80000,





065.854

#### MGBGT FROM 1968 ON REAR BRAKE CYLINDER Rear Brake Cylinder for either side of MGB GT from 1968 on. Original Equipment Part no. was GWC1122 065.837





**RH BRAKE CYLINDER** 

#### MINI MK II 1964-1984 (0.9375 IN) FRONT LH BRAKE CYLINDER

Brake Cylinder for the front left hand twin leading shoe drum brake of Mini Mk II from 1967 to 1984 with bore size 0.9375 in. Sold singly but 2 required per wheel. (Left hand means the left hand side as viewed from the driving seat). Original Equipment Part No. GWC127. (For the right hand cylinder refer to 065.777)

065.778

### **BRAKE FLUIDS**

to 065.778

065.777





#### **CASTROL UNIVERSAL DOT 4 BRAKE & CLUTCH FLUID**

A DOT4 synthetic brake fluid with a boiling point of 270 °C. Compatible with all existing natural and synthetic rubber seals and metals used in conventional braking systems. It has good anti vapour lock properties. Suitable for all classic cars including those with disc brakes, but not Citroen or Rolls-Rovce 1 litre

FOR LATEST PRICES REFER TO WEBSITE



characteristic makes it most suitable for high performance vehicles. Exceptional anti-corrosion and anti vapour lock performance. (Replaces Castrol Racing and Castrol Super Disc Brake fluids). 1 litre

090.934



090.930

**MILLERS UNIVERSAL BRAKE FLUID DOT 4** A high boiling point universal brake and clutch fluid. For a II braking systems where a non-mineral fluid is required. Suitable for use at the higher temperatures seen in modern braking systems. 500ml 090.933





FOR LATEST PRICES REFER TO WEBSITE

# **BRAKE CYLINDERS**



MGC 1967-69 REAR BRAKE CYLINDER Rear Brake Cylinder for either side of MGC 1967 69. Original Equipment Part No. GWC1117

MG TD AND TF FRONT BRAKE CYLINDER Brake Cylinder for the front drum brakes of MG TD/TF. The same part is used on both the right and left hand wheels. Original Equipment Part No. LK30284 065.774



#### MINI MK II 1967-1984 (0.9375 IN) FRONT

Brake Cylinder for the front right hand twin leading shoe drum brake of Mini Mk II from 1967 to 1984 with bore size 0.9375 in. Sold singly but 2 required per wheel. (Right hand means the right hand side as viewed from the driving seat). Original Equipment Part No. GWC126. (For the left hand cylinder refer

#### SPRITE MK II AND MIDGET MK I (LATE) **REAR BRAKE CYLINDER**

Rear Brake Cylinder (double acting piston type) for either side of Austin Healey Sprite Mk II from HAN6 20792 (when fitted with front drum brakes) and MG Midget Mk I from GAN1 13555 (when fitted with front drum brakes). Original Equipment Part No. GWC1115

065.831



**CASTROL SUPER DOT 4 BRAKE FLUID** 

point of 280 degrees C. This higher temperature

#### **CASTROL SRF FULL RACE SPECIFICATION BRAKE FLUID**

With a boiling point at least 300 degrees C this special brake fluid is of special value in competitive motor sport where extreme braking conditions are encountered. 1 litre

090.908



### PENRITE SILICONE BRAKE FLUID DOT 5

Silicone Brake Fluid is a Premium quality, fully Synthetic silicone Brake Fluid designed for use where DOT 5 Silicone brake fluids are required. It fully meets the requirements of the US FMVSS 116 DOT 5 Specification. 500ml



015.934

LIGHTING

SWITCHES

IGNITION

WIRING

HEATERS & ELECTRIC

ACCESSORIES

BODY HARDWARE

#### BRAKES & SUSPENSION

CLUTCH KITS

EXHAUSTS

FIXINGS

FUFL SYSTEMS & FILTERS

MIRRORS

POWER STEERING

SEATS & SEAT BELTS

WASHERS & WIPERS

OIL & AIR FILTERS

CARE & STORAGE

OIL, GREASE & FLUIDS

PAINT & ANTI-RUST